



## T2380

## Powerful & Rugged for Heavy Duty Operation



**Tally** 

- Full range of automatic features to minimize user intervention
- Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard.
- Optional Interfaces: RS232 Serial; Coax/Twinax;
   Ethernet IPDS Straight through paper path for easy forms loading
- Compatible with a wide range of operating systems including Wiindows, UNIX, DOS, SAP R3 and legacy systems

"Unsurpassed excellence". That defines the rugged high powered T2380 printer. Built to leave a lasting impression on your productivity, this high speed workhorse exemplifies what rugged durability is all about. With its advanced 24-pin print head, the 2380 is engineered to perform at a blistering pace even in the harshest of operating environments. You're assured of top-shelf performance, crisp, clear and reliable print quality and a machine you can count on when your performance is what counts.

Low running costs and durability in the harshest of print environments make these products excellent value for money. These products are well matched to Microsoft Windows applications, and highly compatible with other host operation environments including legacy systems.

Fully automated operation, coupled with the ,straight through' paper path, allows ease of use and virtually eliminates errors caused by user intervention.

Available Configuration:

T2380
T2380 2T with additional rear tractor
T2380 IGP with IGP/PJL Support

## T2380

Print Speed	At 10, 12 cpi: High Speed Draft 800, 1000; Draft 667, 800; NLQ 222, 267
Throughput	627 pages per hour (ECMA 132)
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (Emulation dependent)
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	750 million characters (draft)
Memory	128Kb
Standard Connectivity	Bi-directional parallel plus Ethernet 10/100BaseT with 128Kb buffer
Optional Connectivity	RS232 Serial, Adapters, Twinax/Coax, Ethernet IPDS
Standard Emulation	BM® Proprinter, Epson® LQ (ESC P/2), Genicom ANSI, MTPL + Barcode/LCP IGP Version: IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
Optional Emulation	PCL3 (rugged writer)
Fonts	HS Draft, Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, Kix/Royal, OCR A, OCR B, 22 Bar Codes & scaleable LCP
Consumables	20 million characters
STD Paper Handling	Push tractor with paper parking and AGA; 2nd rear push tractor - T2380-2T only
Optional Paper Handling	2nd front tractor (user installable), paper pedestal, paper basket, paper cutting
	device
Paper Type	Continuous forms
Paper Weight	Tractor front max 120g/m² single part form
Paper Size	Length: 3" min, 22" max; Width: 3" min, 16.5" max
Physical Weight	Approximately 45.6 lbs (20.7kg)
Physical Size	24.5" x 11" x 17" (623 x 280 x 432 W x H x D mm)
Power Voltage	120V/230V
Power Consumption	60W printing
Workload	50,000 pages per month
Number of Copies	Up to 6-part forms; 2-part forms for rear tractor of T2380-2T
Temperature	+10° to +35°C
Humidity	20% to 80%
Acoustic	59dB(A)
Warranty	90 day on-site warranty
Option 1	2nd front tractor (user installable), paper pedestal, paper basket, paper cutting
	device

Note: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOMprior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.

## **DASCOM Americas Corporation**

421 West Main Street Waynesboro, Virginia USA 22980-3606 Tel:877 434 1377 www.dascom.com Copyright © 2010 DASCOM Americas Corporation All rights reserved. All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

